

CHEMTEQ[®]

Formaldehyde Vapor
Breakthrough Indicator
Inline
HCHO BTI Inline
(PN: 606)



SPECIFICATION



Formaldehyde BTI Inline Specifications

1. Application

The Formaldehyde BTI inline (PN: 606) is qualitative (yes/no) colorimetric indicator for real-time indication of formaldehyde vapor.

2. Specifications

- | | |
|-------------------------------|---|
| a. Weight: | 28g (1.0oz) |
| b. Dimensions: | 89.9mm (3.5in), diameter 24.5mm (1.0in) |
| c. Inlet & outlet dimensions: | ¾" MNPT |
| d. Operating temperature: | -20°C to 55°C (-4°F to 131°F) |
| e. Operating humidity: | 5% RH to 90%RH |
| f. Minimum detectable limit: | 0.4ppm-hr at 30 cm/sec face velocity |
| g. Color change: | Brown to dark blue |
| h. Storage temperature: | 4°C to 25°C, (39°F to 77°F) |
| i. Shelf life: | 1 years at 4°C to 25°C, (39°F to 77°F) |
| j. Service life: | 1 year |

Cross interferences: Acrolein and aldehydes found in cigarette smoke react with approximately the same sensitivity. No other interferences are known.

3. Instructions

- Ensure that packaging pouch is intact.
- Open packaging pouch by tearing off the top part from one of side notches.
- Remove the BTI Inline from the packaging pouch.
- Remove the protective red plugs to activate the breakthrough indicator.



Caution: Only hand tighten indicator into tubing

- Formation of dark blue color indicates the presence of formaldehyde vapor.

YOU CAN REUSE THE EXHAUSTED FORMALDEHYDE VAPOR BTI INLINE BY REPLACING THE CONSUMED FORMALDEHYDE VAPORS INDICATOR ASSEMBLY WITH A FRESH INDICATOR ASSEMBLY (PN: 606-1600). PLEASE CONTACT US FOR DETAILS.



CHEMTEQ[®]

Chemteq, Inc., 600 West 24th Street, Suite B, Norfolk, Virginia 23517, Tel 757-622-2223, sales@chemteq.net
©2009 Chemteq, Inc.

www.chemteq.net

MP-6068100-081420-C