## CHEMTEQ

Hydrogen Sulfide Breakthrough Indicator Sticker For Sewer Manhole Filters H<sub>2</sub>S (BTIS SMF) (PN: 148-0000)



Replace Filter

Over Exposed



## 1. Application

The Hydrogen Sulfide BTIS SMF (PN: 148-0000) is qualitative (yes/no) colorimetric indicator for the saturation and end-of-service life of sewer manhole filters. The indicator is designed to provide real-time indication of the breakthrough of hydrogen sulfide gas. Rain and drainage water have no effect in the performance of the BTIS SMF.

2. Specifications

a.	Weight:	0.4g (0.02oz)
b.	Dimensions:	2.8mm (0.11in),φ: 38.1mm (1.5in)
c.	Operating temperature:	-40°C to 65°C (-40°F to 149°F)
d.	Operating humidity:	5% RH to 95%RH
e.	Minimum detectable limit:	1ppm•hr at 30 cc/sec face velocity
f.	Color change:	Green to brown to black
g.	Storage temperature:	4°C to 30°C, (39°F to 86°F)
h.	Water effect:	waterproof
i.	Sunlight effect:	no effect
j.	Shelf life:	2 years at 4°C to 25°C, (39°F to 77°F)
k.	Service life:	2 years

Cross interferences: None known.

## 3. Operating Instructions

- a. Ensure that packaging pouch is intact.
- b. Open packaging pouch by tearing off the top part from one of side notches
- c. Remove indicator sticker from the packaging pouch.
- d. Peel off the protective liner to expose the bottom adhesive (Figure 1).



- e. Hold the sticker from the edges, as shown in Figure 2, and place it on center clean area of the filter's outlet with the reading area (glossy surface) of the sticker facing up.
- f. Press firmly to attach sticker to the filter's outlet (Figure 3).
- g. Replace filter when the reading area of the indicator changes color to brown or black.



Figure 1

Figure 2

Figure 3

## CHEMIEQ

Chemteq, Inc., 600 West 24<sup>th</sup> Street, Suite B, Norfolk, Virginia 23517, Tel 757-622-2223, sales@chemteq.net ©2009 Chemteq, Inc. WWW.chemteq.net MP-1488100-091820-C